



P.C.B LAYOUT
BOTTOM VIEW

CIRCUIT DIAGRAM

ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

RATING	0.3A 50V DC
CIRCUIT	2P4T
CONTACT RESISTANCE	100mΩ MAX.
TIMING	NON-SHORTING
TRAVEL	2mm
OPERATING FORCE	500±150gf
OPERATING LIFE(cycles)	10,000

8					WITHIN 1.5mm: ±0.1mm	UNITS	mm	TITLE: 龙创中业电子(深圳)有限公司		PART NO.:	SK-24D03
7	SPRING PLATE	SUS	1		OVER 1.5mm: ±0.2mm	MAT'L	SEE NOTE	SLIDE SWITCH / HORIZONTAL		DWG NO.:	ADL-24D03
6	CONTACT CLIP	PBS STRIP	2			FINISH	SEE NOTE	DR: <i>Stacy</i> 2016/07/15		SCALE	SHEET 1/1
5	TERMINAL	BRASS STRIP	12				SEE NOTE	CHKD: <i>Stacy</i> 2016/07/15		REV.	A
4	BASE	PHENOLIC RESIN	1					DR: <i>Stacy</i> 2016/07/15		SCALE	SHEET 1/1
3	KNDB	POM	1					APPD:		REV.	A
2	FRAME	STEEL STRIP	1					APPD:		REV.	A
1	PARTS	MATERIAL	Q'TY	FINISHING				APPD:		REV.	A

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED, COPIED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS WITHOUT THE WRITTEN CONSENT OF ACCURATE INNOTECH INC.