

產品規格圖 (STANDARD OF PRODUCTS)

產品類別(CATOLOGE): 電流過載保護器(SUPPLEMENTARY PROTECTOR)
產品名稱(NAME): RFLB
規格(STANDARD): UL1077 AND IEC60934
材質(MATERIAL): PHENOLIC
電流(CURRENT RATING): 3~40A
電壓(VOLTAGE RATING): 125V/250V AC/ 32VDC
產品認證(APPROVALS): UL/CUL/CSA/TUV/CCC



規 格 圖 (SPECIFICATION)

Panel Hole	M11X1.0	M12X1.0	Panel Cutout Thickness: 0.6~2.5mm (Snap-in Type)		
Bushing Type					
	Metal(金屬)	Metal(金屬)	Plastic(塑膠)	Plastic(塑膠)	Plastic(塑膠)
thread	M11XP1	M11XP1	M12XP1		
No.	A Type	B Type	C Type	D Type	F Type
Mounting Cap					
	1 Type	2 Type	3 Type	4 Type	5 Type
Terminal Type					
	A Type: Straight	B Type: Line	C Type: Pin	D Type: Load Pin	E Type: 90° Bend

RFLB	1	0	3	1	2	C	3	B	—	B	A
Rating	Voltage		Panel Hole	Bushing Type	Mounting Nameplate Type		Print	Button	Terminal		
RFLB	03-3A	3~C	12-250V/DC 3V	11-M11	A-A Type	N-None	N-None	—: No Print	B-Block	A-A Type	
RFLBA	2	(PHENOLIC)		12-M12	B-B Type	1-1 Type	A-Embossed	D: White(白)	R-Red	B-B Type	
	40-40A	1~C	12-250V/DC 3V	03-Snap	C-C Type	2-2 Type	B-Silver Printing on Black	1: Black(黑)	W-White	C-C Type	
			1000-(12 0.5/0.1)	0-Auto Reset	D-D Type	3-3 Type	2: Red(紅)	2: Red(紅)	N-No Button	D-D Type	
系列名稱					E-E Type	4-4 Type	C-Black Printing on Silver	3: White(白)		E-E Type	
規格					F-F Type	5-5 Type		4: Black(黑)		F-F Type	
								5: Red(紅)		G-G Type	
								6: White(白)		H-H Type	
								7: Black(黑)		I-I Type	
								8: White(白)		J-J Type	
								9: Red(紅)		K-K Type	
								A: White(M123mm)		L-L Type	
								B: White(M789mm)		M-M Type	
										N-N Type	
										O-O Type	
										P-P Type	
										端子型式	

RFLB專用
 Rating: 3-40A 125V-250V AC/32V DC
 Approvals: UL/eUL/TUV/CCC/CSA
RFLBA專用
 Rating: 3-40A 125V-250V AC/32V DC
 Approvals: UL/eUL/TUV